

# Beta Pendant LED

Project: - Mavis Tires  
 Type: -  
 Qty: 1  
 Series: BPL - R4 - 2C - 4TL500 - 45 - TBD - TBD - Options  
 Mounting: Light Engine CCT Finish Voltage Options  
 Pole Series: A35 - 12 - TBD - Pole Options

Series	Optics	Mounting	Light Engine	CCT	Finish	Voltage	Options
BPL - R1	Typ I	Style	4TL500 3500K/4.0W	30 3000K	WR White	RS	Route 508 Street
BPL - R2	Typ II	2C	4TL500 5000K/5.0W	40 4500K	BZ Bronze	SP	Photo Cell
BPL - R3	Typ III	3C	4TL500 5000K/5.0W	40 4500K	SV Silver	SP	Photo Cell
BPL - R4	Typ IV	4C	4TL500 5000K/5.0W	40 4500K	SP Premium	SP	Photo Cell
BPL - R5	Typ V	W	4TL500 5000K/5.0W	40 4500K	CPair	SP	Photo Cell



**1. Mounting:** - The mounting arm is made of aluminum and is attached to the pole via a clamp. The mounting arm is adjustable and can be rotated 360 degrees.

**2. Fixture Connection:** - The fixture is connected to the pole via a clamp. The fixture is adjustable and can be rotated 360 degrees.

**3. Pole:** - The pole is made of aluminum and is adjustable. The pole is available in various heights and finishes.

**4. Optics:** - High performance LED optics are available in various finishes and colors. The optics are adjustable and can be rotated 360 degrees.

**5. LED Driver:** - The LED driver is made of aluminum and is adjustable. The driver is available in various voltages and wattages.

**6. Pole Protection:** - The pole is protected by a powder coat finish. The finish is available in various colors and finishes.

**7. LED Driver:** - The LED driver is made of aluminum and is adjustable. The driver is available in various voltages and wattages.

**8. Pole Protection:** - The pole is protected by a powder coat finish. The finish is available in various colors and finishes.

**9. Pole Protection:** - The pole is protected by a powder coat finish. The finish is available in various colors and finishes.

## A35 3 1/2" Round Straight Aluminum Pole

Project: - Mavis Tires  
 Type: -  
 Qty: 7

Ordering Format:	A35	12	TBD	Options
Series	Height	Finish	Options	Options

Wall Thickness	EPA Information (ft)	Finish	Options
0.015	0.015	WR White	BCT Bronze or CEI
0.015	0.015	BK Black	Arctic Blue
0.015	0.015	BZ Bronze	REC 2000
0.015	0.015	SV Silver	SP Premium
0.015	0.015	CPair	Other

**Standard Specifications:** - All poles are constructed per ANSI A92.1 standards for vertical ladders. All poles are made of aluminum. The poles are adjustable and can be rotated 360 degrees.

**Anchor Base:** - The anchor base is made of aluminum and is adjustable. The anchor base is available in various sizes and finishes.

**Access Hole:** - The access hole is made of aluminum and is adjustable. The access hole is available in various sizes and finishes.

**Anchor Bolt:** - The anchor bolt is made of aluminum and is adjustable. The anchor bolt is available in various sizes and finishes.

**Base Cover:** - The base cover is made of aluminum and is adjustable. The base cover is available in various sizes and finishes.

NTL Limited (In. U.S.A.)  
 1300 S. Main Street  
 Erie, PA 16512  
 814-831-5000  
 www.selux.com

# ALBANY POST ROAD (NYS RTE 9)



## A35 3 1/2" Round Straight Aluminum Pole

Project: - Mavis Tires  
 Type: -  
 Qty: 7

Ordering Format:	A35	12	TBD	Options
Series	Height	Finish	Options	Options

**Anchor Bolt Detail:** - The anchor bolt is made of aluminum and is adjustable. The anchor bolt is available in various sizes and finishes.

**Base Covers:** - The base covers are made of aluminum and are adjustable. The base covers are available in various sizes and finishes.

**Optional Accessories:** - The optional accessories include photo cell sensors, motion detectors, and other smart lighting solutions.

NTL Limited (In. U.S.A.)  
 1300 S. Main Street  
 Erie, PA 16512  
 814-831-5000  
 www.selux.com

**NOTES:**  
 DUE TO VARIATIONS IN LAMPS, BALLASTS, MANUFACTURING, LINE VOLTAGE AND SITE CONDITIONS, A GUARANTEED LEVEL OF PERFORMANCE IS NOT POSSIBLE AND IS NOT REPRESENTED BY THIS ANALYSIS.

1. THE RESULTS OF THIS STUDY ARE TO BE VIEWED AS POSSIBLE AND NOT REPRESENTED BY THIS ANALYSIS.

2. LIGHT LOSS FACTORS (LLF) ARE AS NOTED IN SCHEDULE.

5 LUMEN LANE  
 P.O. BOX 1060  
 HIGHLAND, NY 12528  
 PH. (845) 691-7723

JOB NAME:  
 Mavis Tires -Hyde Park Town Center

LOCATION:  
 Hyde Park, NY

PREPARED FOR:  
 LightSpec

SELUX REPRESENT:  
 GP

DRAWN BY:  
 LLS

Page 1 of 1

Rev B1

Date: 9/7/2016

Luminaire Schedule Symbol	Qty	Label	Arrangement	Total Lamp Lumens	LLF	Description	Mounting Height
(Symbol)	6	BPL-W	SINGLE	4656	0.900	BPL-W-4TL500-R4-45	12'
(Symbol)	6	BPL-1	SINGLE	4656	0.900	BPL-1-4TL500-R4-45	12'
(Symbol)	1	BPL-2	BACK-BACK	4656	0.900	BPL-2-4TL500-R4-45	12'

Label	CalcType	Units	Avg	Max	Min	Avg/Min	Max/Min
Rowway CalcPts	Illuminance	Fc	2.11	5.8	0.6	3.52	9.67
Spill Light CalcPts	Illuminance	Fc	0.00	0.1	0.0	N.A.	N.A.
Walkway CalcPts	Illuminance	Fc	2.39	4.9	0.6	3.98	8.17